
Technical data sheet 90° bend 110 FT

Item number: 6036832



90° bend for the creation of a horizontal branch, fitting for lock and screw-on cable trays of side height 110 mm. Screwless mounting with double clamps or screw connection with FRS truss-head screws and M6 combination nuts. Can be used indoors and outdoors. Fastening material must be ordered separately.



CER

St

Steel



Hot-dip galvanised

Master data

Item number	6036832
Туре	RB 90 115 FT
Description 1	90° bend
Description 2	for cable tray, horizontal
Manufacturer	ОВО
Dimension	110x150
Colour	zinc
Material	Steel
Surface	Hot-dip galvanised
Surface standard	DIN EN ISO 1461
Smallest sales unit	1
Unit of quantity	Piece
Weight	115.5 kg
Weight unit	kg/100 pc.
CO2 Footprint (GWP) Cradle-to- Gate	3,393 kg CO2e / 1 Piece

Technical data sheet 90° bend 110 FT



Item number: 6036832

Dimensions 90 146 275

Width	150 mm
Height	110 mm
Plate thickness	0.8 mm
Dimension B	150 mm
Dimension R	50 mm

Technical data

Bend (angle)	90°
Connector version	Integrated connector
Туре	Bend, rigid
Maintain electrical functions	no
Material thickness, floor plate	0.8 mm
Mounting perforation in base	yes
NATO hole pattern	no
Change of direction	Horizontal
Rustproof steel, pickled	no
Side perforation	yes
Permitted temperature range, max.	120 °C
Permitted temperature range, min.	-20 °C
Wide-span version	no
Type of connector, cable support system	screwed/clamped
Recommended quantity of bolts	18 St.
Rail thickness	1.25 mm