# Technical data sheet

90° bend 60 FT

**Item number: 6036600** 



90° bend for the creation of a horizontal branch, fitting for lock and screw-on cable trays of side height 60 mm. Screwless mounting with double clamps or screw connection with FRS truss-head screws and M6 combination nuts. Can be used indoors and outdoors. Fastening material must be ordered separately.



# CER

St

Steel



Hot-dip galvanised

### Master data

Item number	6036600
Туре	RB 90 650 FT
Description 1	90° bend
Description 2	for cable tray, horizontal
Manufacturer	OBO
Dimension	60x500
Colour	zinc
Material	Steel
Surface	Hot-dip galvanised
Surface standard	DIN EN ISO 1461
Smallest sales unit	1
Unit of quantity	Piece
Weight	339.3 kg
Weight unit	kg/100 pc.
CO2 Footprint (GWP) Cradle-to- Gate	10,454 kg CO2e / 1 Piece

## **Technical data sheet**

### 90° bend 60 FT

**Item number: 6036600** 



# Dimensions 90 496 625

Width	500 mm
Height	60 mm
Plate thickness	0.8 mm
Dimension B	500 mm
Dimension R	50 mm

### Technical data

Bend (angle)	90°
Connector version	Integrated connector
Type	Bend, rigid
Maintain electrical functions	no
Material thickness, floor plate	1 mm
With cover	no
Mounting perforation in base	yes
NATO hole pattern	no
Change of direction	Horizontal
Rustproof steel, pickled	no
Side perforation	yes
Permitted temperature range, max.	120 °C
Permitted temperature range, min.	-20 °C
Wide-span version	no
Type of connector, cable support system	screwed/clamped
Recommended quantity of bolts	16 St.
Rail thickness	1.25 mm