Technical data sheet

Support profile for PV module mounting, free-standing system

Item number: 5900504





Support profile to mount photovoltaic modules on free-standing systems. Mounting of support profile on pre-mounted supports with KV FT cross-connectors. Mounting of the PV modules on the support profile with end and/or connection clamps. Connection of multiple support profiles with LV FT straight connectors and KV FT cross-connectors, screw-on.



Hot-dip galvanised

Master data

| Item number | 5900504 |
|--|---------------------------|
| Туре | TP 1020 FT |
| Description 1 | Truss profile |
| Description 2 | for free-standing system |
| Manufacturer | OBO |
| Dimension | 40x80x5760 |
| Colour | zinc |
| Material | Steel |
| Surface | Hot-dip galvanised |
| Surface standard | DIN EN ISO 1461 |
| Smallest sales unit | 1 |
| Unit of quantity | Piece |
| Weight | 1940 kg |
| Weight unit | kg/100 pc. |
| CO2 Footprint (GWP) Cradle-to- Gate | 39,6396 kg CO2e / 1 Piece |

Technical data sheet

Support profile for PV module mounting, free-standing system



Item number: 5900504



Technical data

| Cable duct, integrated | no |
|------------------------|-----------------------|
| Cable duct optional | no |
| Section modulus Sx | 10600 mm ³ |
| Section modulus Sy | 5200 mm ³ |
| Module width min. | 1010 mm |
| Module width max. | 1020 mm |