### **Technical data sheet**

# Junction box T40, with knock-out entries, with terminal

**Item number: 2007904** 



Junction box for the connection of cables and lines indoors and in protected outdoor areas. Square design with knock-out entries to the sides and knock-out entries in the bottom. Suitable for wall and ceiling mounting and on mounting panels. With the option to fasten inside and to mount via the corner domes. With fixed clamping cover. Made from halogen-free and UV-resistant materials. Junction box according to DIN EN 60670. Flame-resistant to DIN EN 60695/2/11, test temperature 650  $^{\circ}\text{C}.$  Impact resistance IK07 according to DIN EN 50102.

Clear internal dimensions: 77x77x46 mm



















Polypropylene

R/A		ter	٨,	-+-
IVI	as	Lei	u	ala

Item number	2007904	
Description 1	Junction box	
Description 2	M20 entry + terminal strip	
Manufacturer	OBO	
Dimension	90x90x52	
Colour	Light grey; RAL 7035	
Material	Polypropylene	
Smallest sales unit	5	
Unit of quantity	Piece	
Weight	8.2 kg	
Weight unit	kg/100 pc.	
CO Footprint (GWP) Cradle-to- Gate	0,2692 kg COe / 1 Piece	

# **Technical data sheet**

# Junction box T40, with knock-out entries, with terminal strip





# Dimensions 28 28 90

Length	90 mm
Width	90 mm
Height	52 mm

### Technical data

Expandable	yes		
No. of entries	7		
Number of terminals	5		
Type of insertion	Plug-in seal		
Type of entry	Gland		
Type of housing penetration	Pre-marking		
Measured insulation voltage Vi	500 V		
Equipment	Without		
Cover	Not transparent		
Cover fastening	Locking		
Entry from rear	yes		
Entries	7 x Ø20		
Explosion-tested version	no		
Flame-resistant	acc. to VDE 0471/DIN 695 Part 2-1, test temperature 650°C		
Shape	Square		
Maintain electrical functions	Without		
For Ex zone	Without		
For Ex zone gas	Without		
For Ex zone dust	Without		
Fibre-glass reinforced	no		
Halogen-free	yes		
Clear internal dimensions	77x77x46 mm		
With screening	no		
with lid	yes		
Mounting type	Wall/ceiling mounting		
Nominal cross-section, min.	4 mm <sup>2</sup>		
Nominal voltage	500 V		
Sealable	yes		
Protection rating	IP67		
Protection rating IK code	IK07.		
Permitted temperature range, max.	60 °C		

# **Technical data sheet**

Junction box T40, with knock-out entries, with terminal strip

**Item number: 2007904** 



Technical data		
	Permitted temperature range, min.	-5 °C
	Weatherproof	no