## **Technical data sheet Empty housing X 04**

**Item number: 2005598** 





Master data

Junction box for the connection of cables in indoor and outdoor areas. Square design without entries. Suitable for wall and ceiling mounting with the option to fasten outside, inside or to mount via the corner domes. Particularly impact resistant with IK09. Cover with quick lock, sealable. Made from halogen-free and UVresistant materials.

Junction box according to DIN EN 60670. Impact resistance IK09 according to DIN EN 50102. Protection rating IP67 according to DIN EN 60529.













kg/100 pc.

1,0409 kg COe / 1 Piece





Weight unit

CO2 Footprint (GWP) Cradle-to-Gate

Polycarbonate

Item number	2005598
Туре	X04C SW
Description 1	Empty Enclosure
Manufacturer	OBO
Dimension	114x114x78
Colour	Graphite black; RAL 9011
Material	Polycarbonate
Smallest sales unit	1
Unit of quantity	Piece
Weight	26.3 kg


## Technical data sheet Empty housing X 04





## 

Height



## **Technical data**

114

Extension option	no
Cover fastening	Screwed
Shape	Square
Suitable for outdoor use	yes
Clear internal dimensions	102x102x60 mm
with lid	yes
Mounting type	Surface-mounted
Protection rating	IP67
Protection rating IK code	IK09
Protection class	II
Permitted temperature range, max.	60 °C
Permitted temperature range, min.	-5 °C
Weatherproof	yes

78 mm