Technical data sheet Junction box X 06

Item number: 2005152





Junction box for the connection of cables and lines indoors and in outdoor areas. Rectangular design with knock-out entries. Suitable for wall and ceiling mounting with the option to fasten outside, inside or to mount via the corner domes. Particularly impact resistant with IK09. Cover with quick lock, sealable. Made from halogen-free and UV-resistant materials.

Junction box according to DIN EN 60670. Flame-resistant to DIN EN 60695/2/11, test temperature 650 °C. Impact resistance IK09 according to DIN EN 50102. Protection rating IP67 according to DIN EN 60529.



Master data


	Item number	2005152
	Description 1	Junction box
	Description 2	with red cover
	Manufacturer	OBO
	Dimension	150x116x86
	Colour	Black / red
	Material	Polycarbonate
	Smallest sales unit	1
	Unit of quantity	Piece
	Weight	33.5 kg
	Weight unit	kg/100 pc.
	CO Footprint (GWP) Cradle-to- Gate	1,3296 kg COe / 1 Piece

Technical data sheet Junction box X 06

Item number: 2005152



Dimensions Length 151 mm Width 117 mm Height 86 mm



Technical data

56

yes Expandable No. of entries 8 Type of entry Cuttable stepped membrane Type of housing penetration Pre-marking Measured insulation voltage Vi 750 V Not transparent Cover Cover fastening Screwed Entry from rear no 4 x Ø20/25, 4 x Ø20/25/32 Entries Explosion-tested version no acc. to VDE 0471/DIN 695 Part 2-1, test temperature 650°C Flame-resistant Shape Rectangular Fibre-glass reinforced yes yes Halogen-free 137x105x68 mm Clear internal dimensions Max. Conductor cross-section 6 mm² With screening no with lid yes Mounting type Wall/ceiling mounting Nominal cross-section, max. 6 mm² Nominal cross-section, min. 2.5 mm² Nominal voltage 750 V Sealable yes Impact-resistant yes Protection rating IP67 Protection rating IK code IK09 Permitted temperature range, 60 °C max.

Item number: 2005152

Technical data

Permitted temperature range, min.	-5 °C
Weatherproof	yes

